


## RATING AND CHARACTERISTICS

Standard Varistors - 53mm

Ordring Code 	Varistor Voltage at 1mA	Maximum Allowable Voltage		Maximum Clamping Voltage		Withstanding Surge Current (8/20us)	Energy (10/1000us)
	DC (V)	AC rms (V)	DC (V)	Vc (V)	IP (A)	1 Time (A)	(J)
JVR 53N 201K □△△	200 (185~225)	130	170	340	500	60000	600
JVR 53N 241K □△△	240 (216~264)	150	200	395			720
JVR 53N 271K □△△	270 (243~297)	175	225	455			810
JVR 53N 331K □△△	330 (297~363)	210	275	550		70000	990
JVR 53N 361K □△△	360 (324~396)	230	300	595			1120
JVR 53N 391K □△△	390 (351~429)	250	320	650			1250
JVR 53N 431K □△△	430 (387~473)	275	350	710			1380
JVR 53N 471K □△△	470 (423~517)	300	385	775			1500
JVR 53N 511K □△△	510 (459~561)	320	415	845			1590
JVR 53N 621K □△△	620 (558~682)	385	505	1025			1880
JVR 53N 681K □△△	680 (612~748)	420	560	1120			1880
JVR 53N 751K □△△	750 (675~825)	460	615	1240			1920
JVR 53N 781K □△△	780 (702~858)	485	640	1290			2025
JVR 53N 821K □△△	820 (738~902)	510	670	1355			2100
JVR 53N 911K □△△	910 (819~1001)	550	745	1500			2215
JVR 53N 951K □△△	950 (855~1045)	575	765	1570			2230
JVR 53N 102K □△△	1000 (900~1100)	625	825	1650		2325	
JVR 53N 112K □△△	1100 (990~1210)	680	895	1815		2550	
JVR 53N 122K □△△	1200 (1080~1320)	750	990	1980		2625	
JVR 53N 142K □△△	1400 (1260~1540)	880	1140	2310		2625	
JVR 53N 162K □△△	1600 (1440~1760)	1000	1280	2640	3000		

